

FIC100P-NS-A8

Mind O≠0, I≠I≠1, S≠5, B≠8.

Supply voltage	10...35 V _{DC}
Reverse polarity protection	built-in
Current consumption	<40 mA
Current load capability	200 mA
Output function	— / — ↔ —
Output polarity	NPN
IO-Link	not included
Evaluation principle	static
Resolution	0.6 mm
Switching frequency	5000 Hz
Repeatability	0.1 mm
Sensitivity adjustment	potentiometer
Short circuit protection	built-in, self-resetting
Voltage drop	<1.2 V @ 200 mA
Operating temperature	−20...+55 °C · −3...+132 °F
Ambient light immunity	>100 klx
IP code	IP67
Insulation voltage	500 V
Light source	LED infrared $\lambda=840$ nm
Housing material	zinc die-cast, powder-coated
Switching indicator	LED yellow
Connection	connector M8 Pico
Power-on delay	<0.4 s
Serial mounting	—
Weight	112 g · 4 oz.
Tariff code	85365019
Complies with	CE, RoHS




Fork Light Barrier Contamination-Resistant LED infrared $\lambda=840$ nm · 100 mm fork opening




Warranty Our products are manufactured to stringent ISO 9001 European standards to ensure that our customers only receive the best quality.



Wiring diagram



Pinout



Caution! This device shall not be used if the safety of persons rely on its faultless function.

XECRO reserves the right to make minor changes without prior notification.